

FOCAL LENGTH (EFL):  $84 \pm 0,84$

BACK FOCAL LENGTH (BFL):  $82,39$

1 AR COATING: 980nm V-COAT  
 $R(\text{ABS}) < 0,25\% @ 980\text{nm} @ 0^\circ \text{AOI}$

LEFT SURFACE		MATERIAL	RIGHT SURFACE	
R	$43,43 \pm 0,043 \text{ CX}$	GLASS N-BK7 517/642	R	$\infty \text{ PL}$
$\text{Øe}$	11		$\text{Øe}$	11
3/	3 (0,5) $\lambda=632,8 \text{ nm}$		3/	3 (0,5) $\lambda=632,8 \text{ nm}$
4/	-		4/	1,93'
5/	40 - 20 (MIL-PRF-13830B)		5/	40 - 20 (MIL-PRF-13830B)
6/	-		6/	-

PROTECTIVE CHAMFERS AS NEEDED


ROHS: COMPLIANT    SCALE: NONE     $\lambda = 587,6\text{nm}$

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. DIMENSIONS ARE FOR REFERENCE ONLY

FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

INDICATIONS IN ACCORDANCE WITH ISO 10110

FIRST ANGLE PROJECTION



ALL DIMS IN: mm

**EO**® Edmund Optics®

TITLE 12,0mm Diameter x 84,0mm FL, 980nm V-Coat, PCX Lens

DWG NO 69560

SHEET SIZE A4 SHEET 1 OF 1